


## CABLE UTP CAT 5E (ALEACCION) 100 METROS

C715



| Construction                         |                             |
|--------------------------------------|-----------------------------|
| Jacket                               | PVC-WHITE                   |
| Conductor                            | CCA (Copper Clad Aluminum)  |
| Cond.size                            | 4*2*0.5mm                   |
| Insulator                            | HDPE                        |
| Pair construction                    | Unshielded Twisted          |
| Cable dimensions (AWG - mm)          |                             |
| Length                               | 100M(±5M)                   |
| Electric Specifications              |                             |
| DC Resistance                        | ≤24.5Ω/100M                 |
| DC Resistance Unbalance              | MAX 2.5%                    |
| Mutual Capacitance                   | MAX 5.6NF /100M             |
| Capacitance Unbalance                | Max 330NF/100M              |
| Characteristic Impedance             | 100±15Ω                     |
| Voltage rating (Vrms)                | 30V                         |
| Dielectric Strength                  | 5000mQ/km                   |
| Velocity of Propagation              | 0.62C                       |
| Propagation Delay                    | 536ns                       |
| Propagation Delay Skew               | 45ns                        |
| Ambiental Specifications             |                             |
| Installation Temperature             | -20°C50°C                   |
| Operating Temperature                | -20°C50°C                   |
| Mechanical Specifications            |                             |
| Bending Radius (min)                 | ≥ 8xOD(without load)        |
| Pulling Tension (max)                | ≥12.5MP                     |
| General Specifications               |                             |
| Pair Construction                    |                             |
| Pair Color Codes                     | Blue                        |
|                                      | Orange                      |
|                                      | Green                       |
|                                      | Brown                       |
| Compliance (International Standards) |                             |
|                                      | EIA/TIA 568 & ISO/IEC 11801 |



## DESCRIPCIÓN

- Cable utp cat 5e (aleaccion)
- Ideal para camaras analogicas
- 24awg\*4 pares (aleaccion)
- 100 metros, color blanco
- Bajo norma ul