LENKENG®



HDMI length	≤ 5m
Maximum transfer rate	4.96Gbps
Compatibility	HDMI 1.3，HDCP 1.4
Resolutions	1080P@24/25/30/50/60Hz, 720P@50/60Hz, 576P@60Hz, 480P@60Hz, 1920x1200, 1680x1050, 1600x900, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600
Connection types	One-to-one connection
	One-to-many connection
	Switch cascading
Transmission distance	CAT5 80m / CAT5E 100m / CAT6 120m
Transmission latency	80~130ms
HDMI output	LPCM 2.0
Power Supply	DC 5V/1A
Power Consumption	TX ≤ 3.5W，RX ≤ 3W
Working temperature	- 20℃~60℃
Storage temperature	- 30℃~70℃
Humidity	0~90%RH (no condensation）
Housing	Aluminium(Top cover); Iron(Bottom cover)
Weight	TX：160g，RX：160g
Color	Black
Dimensions	110.0(L)*58.0(W)*26.0(H)mm
Protection	ESD protection
	1a Contact discharge level 2 (±4KV)
	1b Air discharge level 3 (±8KV)
	Implementation of the standard: IEC61000-4-2
	Lightning protection, Surge protection