CONECTOR MECANICO INTELIGENTE SC APC

Y024

DESCRIPCIÓN

- Proyecto FTTH utilizable
- Instalable en campo
- Pérdida de inserción inferior a 0,3 dB
- La cavidad metálica en forma de V funciona bien a altas y bajas temperaturas
- Instalación en menos de 1 minuto
- Rendimiento óptico fiable y superior
- La prueba de tracción del cable cumple con la norma Telcordia GR-326-COR

CARACTERÍSTICAS

ITEM	Technical Parameters
Applicable for	Drop cable / Indoor cable
	0.9mm Tight Buffer Fiber, 2.0mm, 3.0mm Drop Cable
Optical fiber diameter	SM(9/125), MM(50/125, 62.5/125)
	125μm (657A & 657B)
Tight buffer diameter	250μm
Fiber mode	Single mode
Operation time	About 100s(no fiber cut)
Insert loss	⩽ 0.3dB(1310nm & 1550nm)
Return loss	> 50db(PC), > 55db(UPC), > 65db(APC)
Fastening strength of naked fiber	>5 N
Fastening strength of naked fiber holder	>10 N
Tensile strength	>50 N
Using temperature	-40~+75° C
On-line tensile strength (20 N)	IL ⩽ 0.5dB RL ⩽ 5dB
Mechanical durability (500 times)	IL ⩽ 0.5dB RL ⩽ 5dB
Drop-off test (drop-off height 4m,once per direction, totally 3 times)	IL ⩽ 0.3

ESPECIFICACIONES

