

> CARACTERÍSTICAS

Category	U/FTP- CAT6A-4P-PVC-CM			
Reference Standard	ISO/IEC 11801 、 TIA-568-C.2			
Conductor	Material	SOLID-Bare Copper		
	Nom O.D.(mm)	0.560	up down	+0.005 -0.005
Insulation	Material	Skin-foam-skin PE		
	Diameter	1.330±0.05 mm		
Screening Material	Al/Mylar	Drain wire	Yes	
Sheath	Thickness	0.55±0.05 mm		
	External O.D.	7.3±0.5 mm		
	Surface	Clean		
	Material	PVC(complies RoHS),CM		
Surface Printing	Color	TBD		
	Letter height	3.0±0.3mm		
	Color	Black		
	Print error & Space	≤±0.5%, 1m		
Core Color	1 White/Blue	2 White/Orange		
	3 White/Green	4 White/Brown		
Packing	Drum			
Packing length	305±1.5m			
Rip-cord	Yes			
Sheath Physical Properties	Before Aging Tensile Strength (Mpa)	≥13.5		
	Elongation(%)	≥150		
	Aging Period (℃×hrs)	100℃×24h×7d		
	After Aging Tensile Strength(Mpa)	≥12.5		
	Elongation(%)	≥125		
Electrical Characteristics (20℃)	Cold bend(-20±2℃×4h)	8×Cable O.D., No visible cracks		
	Impedance(Ω)	1.0-250.0MHz	100±15	
		250.0-500.0MHz	100±22	
	1.0-500.0MHz Delay Skew (ns/100m)	≤45		
	unbalanced-to-ground capacitance(pf/100m)max	330		
	DC Resistance (Ω/100m) max	9.38		
	DC Conductor Resistance Unbalance (%) max	5.0		

> ESPECIFICACIONES

Technical Performance (100m):				
Frequency (MHz)	RL ≥dB	ATT ≤dB	NEXT ≥dB	PHASE DELAY ≤ns
1	20.0	—	74.3	570
4.0	23.0	3.8	65.3	552
8.0	24.5	5.3	60.8	547
10.0	25.0	5.9	59.3	545
16.0	25.0	7.5	56.2	543
20.0	25.0	8.4	54.8	542
25.0	24.3	9.4	53.3	541
31.25	23.6	10.5	51.9	540
62.5	21.5	15.0	47.4	539
100	20.1	19.1	44.3	538
200	18.0	27.6	39.8	537
250	17.3	31.1	38.3	536
300	16.8	34.3	37.1	536
400	15.9	40.1	35.3	536
500	15.2	45.3	33.8	536

Frequency (MHz)	PSNEXT ≥dB	ELFEXT ≥dB	PSELFEXT ≥dB
1	72.3	67.8	64.8
4	63.3	55.8	52.8
8	58.8	49.7	46.7
10	57.3	47.8	44.8
16	54.2	43.7	40.7
20	52.8	41.8	38.8
25	51.3	39.8	36.8
31.25	49.9	37.9	34.9
62.5	45.4	31.9	28.9
100	42.3	27.8	24.8
200	37.8	21.8	18.8
250	36.3	19.8	16.8
300	35.1	18.3	15.3
400	33.3	15.8	12.8
500	31.8	13.8	10.8

