

> CARACTERÍSTICAS

- Adaptador de corriente universal de sobremesa, apto para diversos productos electrónicos, como sistemas de videovigilancia, luces LED, impresoras POS, sistemas de alarma, etc.
- Entrada de voltaje: CA 100-240 V, 50/60 Hz.
- Diseño con chip de alta calidad.
- Protección contra cortocircuitos y sobrecargas.



Product Model	Z031		Z033	Z035
Type	Universal Plug in Wall Adapter			
Input Voltage	AC 100~240V 50/60Hz			
DC Output	DC 12V 1A	DC 12V 1.5A	DC 12V 2A	DC 12V 3A
Voltage Output Error	12V $\pm$ 5%			
Output Power	12W	18W	24W	36W
DC Cable Length	1.2M			
Housing Material	PC+ABS			
LED Indication	Yes			
DC Connector Size	5.5*2.1mm			
Ripple&Noise	120mV			
Efficiency At Average Load	87% min			
Protection	OVP/SCP/OC/OTP			
Storage Temperature	-20°C to +80°C			
Operating Temperature	-10°C to +40°C			
Product Model	Z032	Z034	Z036	
Type	Universal Desktop Adapter			
Input Voltage	AC 100~240V 50/60Hz			
DC Output	DC 12V 1A	DC 12V 2A	DC 12V 3A	DC 12V 5A
Voltage Output Error	12V $\pm$ 5%			
Output Power	12W	24W	36W	60W
DC Cable Length	1.2M			
Housing Material	PC+ABS			
LED Indication	Yes			
DC Connector Size	5.5*2.1mm			
Split DC Cable	/			4
Ripple&Noise	120mV			
Efficiency At Average Load	87% min			
Protection	OVP/SCP/OC/OTP			
Storage Temperature	-20°C to +80°C			
Operating Temperature	-10°C to +40°C			