

SWITCH DE 8 PUERTOS GIGABIT RJ45

Z051



> CARACTERÍSTICAS

- 8 puertos RJ-45 10/100M (PoE) + 2 puertos RJ-45 10/100M
- Cumple con los estándares IEEE 802.3, IEEE 802.3u e IEEE 802.3af/at
- Potencia máxima de salida PoE: 15,4 W (IEEE 802.3af) / 30 W (IEEE 802.3at)
- Alcance de transmisión PoE de 250 metros para alimentación y datos (Cat. 6)
- Autoadaptación MDI/MDIX
- Conmutación de almacenamiento y reenvío
- Protección contra rayos

> DESCRIPCIÓN

Es un switch PoE avanzado que proporciona un punto de red para la transmisión de datos y la alimentación eléctrica. Cuenta con 8 puertos PoE que pueden suministrar alimentación estándar IEEE 802.3af/at a través de cables de red.

Gracias a su avanzado algoritmo de autosensado para el suministro de energía mediante IEEE 802.3af/at, los equipos conectados, tanto PoE como no PoE, están protegidos de forma segura.

> ESPECIFICACIONES

Model Number				
Port	8*10/100M RJ-45(PoE) +2*10/100M RJ-45			
Network Protocol	IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3af/at			
PoE	PoE Standard	IEEE802.3af/IEEE802.3at		
	PoE Consumption	Max 15.4 W (IEEE 802.3af)/30 W (IEEE 802.3at)		
	PoE Compatibility	IEEE 802.3af/at self-adaptation		
	Output Voltage	DC48V		
	Power Supply	1,2+; 3,6-		
Network Cable	10Base-T: Cat3 UTP/STP(≤100m) 10Base-T: Cat6a UTP/STP(≤250m) 100Base-TX: Cat5e UTP/STP(≤100m)			
Backplane Bandwidth	2Gbps			
Packet Forwarding Rate	Each port 0.1488Mpps			
Buffer Memory	448K			
MAC Size	1K			
Switching	Store-and-Forward			
Power Consumption	150W			
Supply Voltage	AC110-260V input 52V2.88A output			
Light Indicator	PWR	Power indicator light	On	Power-on
			Off	Power-off
	SW	Dial light	Off	Normal mode
			On	VLAN mode
			Flash	Extend mode
	1-10	Link light	On	Link connection
			Flash	Data transfer
Off			Link failure	
Operating Temperature	-20°C to 55°C			
Dimensions (L*W*H)	220*120*45 (mm)			
Gross Weight	0.9kg			
MTBF	100,000 hours			

Ordering Information

Product Type	Part Number	Description
PoE Switch		8*10/100M RJ-45(PoE)+2*10/100M RJ-45; IEEE802.3af/at; Long distance 250 meters(Cat 6)